



**FORMED
TO OUTLIVE
CONDITIONS**

MANUFACTURER OF **RESINS**

ABOUT US

Innovation begins with intention—and at **Amura Polymers**, that intention is clear: to craft resins that empower industries and inspire progress.

Since our founding in 2016, we've grown from a focused operation in Chhatral to a high-capacity, cutting-edge facility in Indrad, Mehsana, scaling from 500 tons to over **3,000 tons per month**. Today, we manufacture a wide spectrum of advanced **alkyds, acrylics, amino resins, and CNSL-based solutions designed to meet the evolving needs of modern industry**.

But growth is only part of the story.

What truly drives us is **curiosity, quality**, and a commitment to helping industries evolve. Our advanced **R&D lab**, guided by global standards, is where ideas become solutions. Whether it's a next-gen industrial coating or a breakthrough in eco-friendly resin technology, we're obsessed with pushing boundaries.

Today, our resins touch everything from paints, varnish, wood coating and auto refinish. We serve clients across India and beyond, with a distribution network that's as strong as the relationships we build.

Because at Amura, it's never just about a product.

It's about chemistry with materials, with innovation, and with people.

We are an **ISO 9001:2015 Certified Company**, recognized for maintaining a robust Quality Management System.



VISION

We envision a world where resin technology doesn't just meet industry demands—it shapes them.

Our vision is to lead that transformation by creating smarter, more sustainable materials that empower innovation across every sector we touch. We want our name to stand for reliability, responsibility, and relentless progress—no matter where our resins go.

MISSION

Our mission is simple yet ambitious:

To engineer resin solutions that solve real-world problems with consistency, creativity, and conscience.

Every day, we commit ourselves to delivering high-performance products that meet exacting standards while reducing environmental impact. We collaborate closely with clients, invest deeply in R&D, and prioritize quality in every step—from raw material to final application.

Because great chemistry isn't just what we make. It's how we work.





PRODUCT CATEGORIES

• Short Oil Alkyds	04
• Medium Oil Alkyds	04
• Long Oil Alkyds	05
• Maliec Modified Rosin Ester	05
• Rosinated Alkyds	05
• Rosin Modified Phenolic Resins	06
• Texture / Hammertone Alkyds	06
• Chain Stop Alkyds / Fast Drying Alkyds.....	06
• Amino Resins	07
• Thermoplastic Acrylic Resins	07
• Thermosetting Acrylic Resins	08
• Acrylic Polyols.....	08
• Modified Alkyds	09
• Cashew Nut Shell Liquid Resins.....	09

SUGGESTED USES

Automotive Refinishing



Enamel Paints



Wood Coating



Road Marking



Industrial Coating





SHORT OIL ALKYDS

Product Code	Oil Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity (FC4 CUP)	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
APC-633	Saturated Fatty Acid Base Alkyd	33	60/70	Xyl/Tolu	250-300 (50% Xylene @ 30°C)	12	3	Stoving enamels, Acid Curing, Wood Coating & NC lacquers.
APCL-631	Lauric Base Alkyd	32	70/80	Xyl/Tolu	180-220 (50% Xylene @ 30°C)	12	1	Non-yellowing white baking enamels, Acid curing, Wood coating & NC lacquers.
APS-681	Soya Base Alkyd	30	55/70	Xyl/Tolu	15-20 Poise (55% Toluene @ 25°C)	12	3	Melamine wood finishes in acid curing systems. Used in NC base finished.
APD-640	DCO Base Alkyd	38	70	Xyl/Tolu	80-120 (50% Xylene @ 30°C)	12	6	General purpose baking enamels for Industrial equipments, Machinery, household appliances and printing inks. Very useful for cold catalysed lacquers with UF Resin used in textile printing screen. Residual hydroxyl of DCO useful as co-reactant in polyurethane finishes.
APTO-630	Toll Oil Fatty Acid Base Alkyd	28	60/70	Xyl/Tolu	140-200 Poise (60% Xylene @ 25°C)	8	6	Fast Drying with Excellent Exterior Durability and Good Stability in Acid curing and NC systems.

MEDIUM OIL ALKYDS

Product Code	Oil Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity 40% Mto FC4 @ 30°C	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
APS-454	Soya Base Alkyd	50	50/60	Mto	80-100	15	6	Air drying alkyd for general purpose industrial enamel.
APS-454	Soya Base Alkyd	50	70	Mto	30-40	15	6	High solid alkyd for air drying synthetic enamel paints.
APL-433	Linseed Base Alkyd	50	60/70	Mto	60-80	10	10	Air drying alkyd for synthetic enamels, primers and undercoats paints.





LONG OIL ALKYDS

Product Code	Oil Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity 50% Mto FC4 @ 30°C	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
APS-318	Soya Base Alkyd	60	60/70	Mto	180-220	12	5	Non-yellowing white for first quality enamels, Roller coatings, Varnishes, etc.
APS-318	Soya Base Alkyd	60	80/100	Mto	120-150	12	5	High solid alkyd for first quality air drying synthetic enamel paints.
APL-381	Linseed Base Alkyd	60	60/70	Mto	95-110	12	10	First quality synthetic enamel paints and printing inks.
APD-309	DCO Base Alkyd	60	70/100	Mto	90-140	12	8	First quality decorative enamel in pastel shades for interior and exterior use. Used for air drying hammer tone finishes.

MALIEC MODIFIED ROSIN ESTER

Product Code	Type	Melting Point	% Non Volatile	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
APMP-552	Maleic modified rosin penta ester gum	100-110 C	100/70	Xyl/Tolu	40-80 Second (50% MTO @ 30°C)	30	12	MTO Compatible used with long/medium alkyd.
APMG-553	Maleic modified rosin glycerin ester gum	100-110 C	100/70	Xyl/Tolu	22-28 Second (50% Toluene @ 30°C)	22-28	10	NC Compatible hence used in NC formulation. Not compatible with MTO.

ROSINATED ALKYDS

Product Code	Oil Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity (40% Mto FC4	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
APD-50R	Rosinated DCO	42	50/60/70	Mto	150-200	25	8	For cost effective decorative enamels for interior and exterior use. Used for air drying furniture enamels.
APL-50R	Rosinated Linseed	43	50/60/70	Mto	150-200	20	12	Decorative enamels in pastel shades for interior and exterior use. Used for air drying furniture enamels.
APL-50R	Rosinated Linseed	43	50/60/70	Mto	80-120	20	12	Decorative enamels in pastel shades for interior and exterior use. Used for air drying furniture enamels.

ROSIN MODIFIED PHENOLIC RESIN



Product Code	Type	Melting Point (Ball & Ring)	% Non Volatile	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-PH-554	Rosin modified Phenolic resin	115-125	100	-	22-28 Second (50% Toluene @ 30°C)	20	12	Paints, Printing Inks, Insulating Varnishes, Oil Varnishes etc.

TEXTURE / HAMMERTONE ALKYDS

Product Code	Oil Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity in FC4	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-SF-718	Soya Base Alkyd	60	80	Xyl/Tolu	90-140 (50% in Mto)	15	10	For Industrial Texture Finish.
AP-DF-709	DCO Base Alkyd	60	80	Xyl/Tolu	90-140 (50% in Mto)	15	10	For Industrial Texture Finish.
AP-SX	Soya Base Alkyd	45	70	Xyl/Tolu	90-140 (50% in Xylene)	15	10	For Hammertone Finish.
AP-DX	DCO Base Alkyd	45	70	Xyl/Tolu	90-140 (50% in Xylene)	15	10	For Hammertone Finish.
AP-LX	Linseed Base Alkyd	45	70	Xyl/Tolu	90-140 (50% in Xylene)	15	10	For Hammertone Finish.

CHAIN STOP ALKYDS / FAST DRYING ALKYDS

Product Code	Fatty Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
APF-145	Fatty Acid Penta Base Alkyd	35	70	Xyl/Tolu	150-200 (50% Xylene @ 30°C)	15	4	Very fast air drying alkyd for auto refinishing. Use in colour retention industrial finishes.
APF-133	Fatty Acid Mixed Polyol Base Alkyd	38	70	Xyl/Tolu	90-140 (50% Xylene @ 30°C)	15	4	Air drying alkyd for auto refinishing. Use in colour retention industrial finishes. Compatible with MTO.
APF-154	Fatty Acid Penta Base Alkyd	40	70	Xyl/Tolu	90-140 (50% Xylene @ 30°C)	15	6	Air drying alkyd for auto refinishing. Industrial stoving enamels, Two pack polyurethane based coating. Compatible with MTO.



AMINO RESINS

Product Code	Type	Free Formal-dehyde %	% Non Volatile ± 2	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-UF-08	Butylated Urea Formaldehyde	1.3	60	N-Butanol	10-20 Poise as Such @ 25°C	3	1	Very fast, low temperature acid curing screen and wood lacquers.
AP-UF-09 (LFF)	Butylated Urea Formaldehyde	0.5	60	N-Butanol	10-20 Poise as Such @ 25°C	3	1	For acid curing wood coatings.
AP-MF-10	Butylated Melamine Formaldehyde	3	60	N-Butanol	07-10 Poise as such @ 25°C	3	1	High gloss stoving enamels with alkyds, epoxy and acrylic systems.
AP-MF-68	Butylated Melamine Formaldehyde	3	60	N-Butanol	08-12 Poise as such @ 25°C	3	1	High efficient, fast curing colour retention stoving enamels resistant to over baking.
AP-MF-70	Butylated Urea Melamine Formaldehyde	3	65	N-Butanol	08-12 Poise as such @ 25°C	3	1	Wide compatibility, low temp curing flexible lacquers for metalized plastic articles. Useful for MTO based finishes and antiwrinkling agent for Rosinated alkyd based stoving finishes.

THERMOPLASTIC ACRYLIC RESINS

Product Code	Type	% Non Volatile ± 2	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-TPA-40	Thermoplastic Acrylic	40	Xyl/Tolu	70-100 Poise as such @ 25°C	7	1	Very fast drying. Excellent colour & Gloss retention. Excellent Weather properties. Resistance to soap and detergent.
AP-TPA-50	Thermoplastic Acrylic	50	Xyl/Tolu	20-30 Poise as such @ 25°C	7	1	
AP-TPA-60	Thermoplastic Acrylic	60	Xyl/Tolu	100-150 Poise as such @ 25°C	15	1	Excellent flexibility, pigment dispersion & plasticizer resistance. High gloss & gloss retention. Good all round Weather properties. Good for exterior concrete applications.





THERMOSETTING ACRYLIC RESIN

Product Code	Type	% Non Volatile ±2	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-TSA-60	Thermosetting Acrylic	60	Xylene / Butanol	10-15 Poise as such @ 25°C	15	1	Low bake stoving system for auto body paints and lacquers. Can also be used for domestic appliance finishing.

ACRYLIC POLYOLS

Product Code	Type	OH Value (On Solid Basic)	% Non Volatile ±2	Solvent	Viscosity in Poise @ 25°C	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-POL-902	Acrylic Resin	70-80	60	Xyl / Ethyl Cello	30-50	10	1	General Purpose PU Coatings with Good Durability.
AP-POL-940	Acrylic Resin	40-50	60	Xyl / Ethyl Cello	25-45	10	1	Suitable for DTM Coating. Very Good Adhesion on Non ferrous metal surfaces like steel, GI, Copper, Brass and Glass Coating.
AP-POL-946	Acrylic Resin	145-155	70	Butyl Ace	40-70	10	1	High Gloss Auto Refinish, Excellent Mechanical and Chemical Properties.
AP-POL-948	Acrylic Resin	80-90	60	Butyl Ace	80-120	5	1	Very Fast Setting good for PU sanding sealer & wood coatings.
AP-POL-949	Acrylic Resin	70-80	70	Xyl	20-30 (40% Xylene In FC4 Cup @ 30°C)	8	1	High Solid & Economical for Base/Top Coat Automotive Finishes.
AP-POL-950	Acrylic Resin	80-90	60	Butyl Ace	30-50	5	1	Top Coat for Wood Coatings with very good gloss, drying & Weather performance.
AP-POL-955	Acrylic Resin	50-60	70	Xyl/C9	22-46	10	1	High Solid, Low Viscosity for General Purpose Industrial and Maintenance Coatings.



MODIFIED ALKYDS



Product Code	Type	Oil Length%	% Non Volatile ± 2	Solvent	Viscosity	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-PU-860	Urethan Alkyd	45	60	Mto	100-140 (50% Mto In FC4 Cup @ 30°C)	8	6	TDI modified for fast drying Alkyd for single pack wood coating enamels for high gloss and abrasion resistance. Urethane Alkyd, 1K PU.
AP-AC-825	Acrylated Alkyd	23	50	Xyl	10-15 Poise as such in Gardner tube @ 25°C	10	4	Very fast drying resins, Excellent outdoor durability. No or very Little drier is required.
AP-ST-830	Styrenate Alkyd	30	50	Xyl	10-15 Poise as such in Gardner tube @ 25°C	10	10	Very fast drying Resistance to Water and mineral oil, primers, Varnishes, hammer finish.

CASHEW NUT SHELL LIQUID RESINS

Product Code	Oil Type	Modified With	% Non Volatile ± 2	Solvent	Viscosity 40% Mto in FC4	Acid Value Max (mgKOH/gm)	Color (Gardner) Max.	Suggested uses
AP-CN-281	CNSL Resin	-	80	Mto	20-30	7	Reddish Brown	Paint, Primer, Liquid Insulating Varnish etc.
AP-CN-282	CNSL Resin	-	70	Xyl	20-30	7	Reddish Brown	Paint, Primer, Liquid Insulating Varnish etc.
AP-CN-284	CNSL Resin	Styrene	70	Styrene	20-30	7	Reddish Brown	Airdrying cum backing Enamel. Coatings for Anti-corrosive properties and for Hamertone finish.
AP-CN-286	CNSL Resin	Alkyd	70	Xyl / Tolu	20-30	10	Reddish Brown	Paints, Printing ink Compositions With High Outdoor durability etc.
AP-CN-288	Cardanol Resin	-	80	Mto	20-30	5	Golden Yellow	Air during cum Banking for dark coloured enamels insulating varnishes, wood polishes etc.
AP-CN-290	Cardanol Resin	Alkyd	70	Xyl / Tolu	20-30	5	Golden Yellow	Paints, Printing ink Compositions With High Outdoor durability etc.



RESIN BASE APPLICATION OPTIONS

RESIN TYPES	PRODUCT CODE	NC WOOD COATING	MEALAMINE WOOD COATING	1KPU	2K PU WOOD COATING	AUTO REFINISH	ARCHITECTURE	PRIMER	INDUSTRIAL/ENAMEL PAINTS	INK	ROAD MARKING	VARNISH	CONCRETE FLOOR/PEVER	HAMMERTONE FINISH
SHORT OIL ALKYDS	APC-633	✓	✓		✓				✓					
	APCL-631	✓	✓		✓				✓					
	APS-681	✓	✓		✓				✓					
	APD-640							✓	✓					
	APTO-630		✓		✓									
MEDIUM OIL ALKYDS	APS-454							✓	✓	✓	✓			
	APS-454							✓	✓	✓	✓			
	APL-433							✓	✓	✓	✓			
LONG OIL ALKYDS	APS-318						✓			✓				
	APS-318						✓			✓				
	APL-381						✓			✓				
	APD-309						✓			✓				
MALLEIC MODIFIED ROSIN ESTER	APMP-552					✓			✓				✓	
	APMG-553	✓	✓											
ROSINATED ALKYDS	APD-50R							✓	✓			✓		
	APL-50R							✓	✓					
	APL-50R							✓	✓					
ROSIN MODIFIED PHENOLIC RESINS	AP-PH-554									✓				
	AP-SF-718												✓	
TEXTURE / HAMMERTONE ALKYDS	AP-DF-709												✓	
	AP-SX												✓	
	AP-DX												✓	
	AP-LX												✓	
	APF-145						✓							
CHAIN STOP ALKYDS / FAST DRYING ALKYDS	APF-133						✓							
	APF-154						✓							
	APF-145						✓							
AMINO RESINS	AP-UF-08	✓	✓											
	AP-UF-09 (LFF)	✓	✓											
	AP-MF-10	✓	✓											
	AP-MF-68	✓	✓											
	AP-MF-70	✓	✓											
THERMOPLASTIC ACRYLIC RESINS	AP-TPA-40								✓					
	AP-TPA-50								✓					
	AP-TPA-60								✓				✓	
THERMOSETTING ACRYLIC RESINS	AP-TSA-60					✓	✓							
	AP-POL-902					✓	✓							
ACRYLIC POLYOLS	AP-POL-940					✓	✓							
	AP-POL-946					✓	✓							
	AP-POL-948					✓	✓							
	AP-POL-949					✓	✓							
	AP-POL-950					✓	✓							
	AP-POL-955					✓	✓							
MODIFIED ALKYDS	AP-PU-860		✓							✓				
	AP-AC-825								✓	✓			✓	
	AP-ST-830								✓	✓			✓	
CASHWE NUT SHELL LIQUID RESINS	AP-CN-281								✓	✓				
	AP-CN-282								✓	✓				
	AP-CN-284								✓	✓				
	AP-CN-286								✓	✓				
	AP-CN-288								✓	✓				
	AP-CN-290								✓	✓				



AIR DRYING



STOVING/BAKING



Amura Polymers Pvt. Ltd.

Office: 18, Sardar Patel Estate, Near Barcelona Arcade,
S P Ring Road, Odhav, Ahmedabad, Gujarat – 382415.

Plant: Survey No. 261, At & Post. Indrad, Tal. Kadi,
Dist. Mehsana. Pin – 382715.

Office Contact

Ph: +91 90332 72911

Sales Contact

Ph: +91 77789 22752

E-mail

info@amurapolymers.com | amurapolymerspvtltd@gmail.com

